
configuration_group_id = configuration_group_id
configuration
configuration_id integer(5) <pk>
configuration_title varchar(64)
configuration_key varchar(64)
configuration_value varchar(255)
configuration_description varchar(255)
configuration_group_id integer(5) <fk>
sort_order integer(5)
last_modified datetime
date_added datetime
use_function varchar(32)
set_function varchar(32)
configuration_group
configuration_group_id integer(5) <pk>
configuration_group_title varchar(64)
configuration_group_description varchar(255)
sort_order integer(5)
visible integer(1)
banners_id = banners_id
banners
banners_id integer(5) <pk>
banners_title varchar(64)
banners_url varchar(64)
banners_image varchar(64)
banners_group varchar(10)
expires_impressions integer(7)
expires_date datetime
date_added datetime
date_status_change datetime
status integer(1)
banners_history
banners_history_id integer(5) <pk>
banners_id integer(5) <fk>
banners_shown integer(5)
banners_clicked integer(5)
banners_history_date datetime
products_id = products_id
categories_id = categories_id
categories_id = categories_id
products_to_categories
products_id integer(5) <pk,fk1>
categories_id integer(5) <pk,fk2>
categories
categories_id integer(5) <pk>
categories_image varchar(64)
parent_id integer(5) <fk>
sort_order integer(3)
date_added datetime
last_modified datetime
categories_description
categories_id integer(5) <pk,fk1>
language_id integer(5) <pk,fk2>
categories_name varchar(32)
languages_id = language_id
products_id = products_id
categories_id = parent_id
reviews_id = reviews_id
tax_class_id = products_tax_class_id
counter
startdate char(8)
counter integer(12)
counter_history
month char(8)
counter integer(12)
currencies
currencies_id integer(5) <pk>
title varchar(32)
code char(3)
symbol_left varchar(12)
symbol_right varchar(12)
decimal_point char(1)
thousands_point char(1)
decimal_places char(1)
sessions
sesskey varchar(32) <pk>
expiry integer unsigned
value text
products_id = products_id
manufacturers_id = manufacturers_id
products
products_id integer(5) <pk>
products_quantity integer(4)
products_model varchar(12)
products_image varchar(64)
products_price decimal(10,2)
products_date_added datetime
products_last_modified datetime
products_date_available datetime
products_weight decimal(7,2)
products_status tinyint(1)
products_tax_class_id integer(5) <fk2>
manufacturers_id integer(5) <fk1>
products_description
products_id integer(5) <pk,fk1>
language_id integer(5) <pk,fk2>
products_name varchar(64)
products_description text
products_url varchar(255)
products_viewed integer(5)
reviews
reviews_id integer(5) <pk>
products_id integer(5) <fk1>
customers_id integer(5) <fk2>
customers_name varchar(64)
reviews_rating integer(1)
date_added datetime
last_modified datetime
reviews_read integer(5)
reviews_description
reviews_id integer(5) <pk,fk1>
languages_id integer(5) <pk,fk2>
reviews_text text
specials
specials_id integer(5) <pk>
products_id integer(5) <fk>
specials_new_products_price decimal(10,2)
specials_date_added datetime
specials_last_modified datetime
manufacturers
manufacturers_id integer(5) <pk>
manufacturers_name varchar(32)
manufacturers_image varchar(64)
manufacturers_id = manufacturers_id
manufacturers_info
manufacturers_id integer(5) <pk,fk1>
languages_id integer(5) <pk,fk2>
manufacturers_url varchar(255)
url_clicked integer(5)
date_last_click datetime
date_added datetime
products_options_id = options_id
products_id = products_id
products_options
products_options_id integer(5) <pk>
language_id integer(5) <pk,fk>
products_options_name varchar(32)
products_options_id = products_options_id
products_attributes
products_attributes_id integer(5) <pk>
products_id integer(5) <fk1>
options_id integer(5) <fk2>
options_values_id integer(5) <fk3>
options_values_price decimal(10,2)
price_prefix char(1)
products_options_values_to_products_options
products_options_values_to_products_options_id integer(5) <pk>
products_options_id integer(5) <fk1>
products_options_values_id integer(5) <fk2>
whos_online
customer_id integer(5) <fk>
full_name varchar(64)
session_id varchar(128)
ip_address varchar(15)
time_entry varchar(14)
time_last_click varchar(14)
last_page_url varchar(64)
customers_id = customer_id
customers
customers_id integer(5) <pk>
customers_gender char(1)
customers_firstname varchar(32)
customers_lastname varchar(32)
customers_dob datetime
customers_email_address varchar(96)
customers_default_address_id integer(5)
customers_telephone varchar(32)
customers_fax varchar(32)
customers_password varchar(40)
customers_newsletter char(1)
customers_id = customers_id
customers_basket
customers_basket_id integer(5) <pk>
customers_id integer(5) <fk1>
products_id text <fk2>
customers_basket_quantity integer(2)
final_price decimal(8,2)
customers_basket_date_added varchar(8)
products_options_id = products_options_id
products_options_values_id = products_options_values_id
languages_id = language_id
products_options_values_id = products_options_values_id
products_options_values
products_options_values_id integer(5) <pk>
language_id integer(5) <pk,fk>
products_options_values_name varchar(64)
customers_basket_attributes
customers_basket_attributes_id integer(5) <pk>
customers_id integer(5) <fk2>
products_id text <fk1>
products_options_id integer(5) <fk3>
products_options_values_id integer(5) <fk4>
languages
languages_id integer(5) <pk>
name varchar(32)
code char(2)
image varchar(64)
directory varchar(32)
sort_order integer(3)
customers_info
customers_info_id integer(5) <pk,fk>
customers_info_date_of_last_logon datetime
customers_info_number_of_logons integer(5)
customers_info_date_account_created datetime
customers_info_date_account_last_modified datetime
address_book
customers_id integer(5) <pk,fk3>
address_book_id integer(5) <pk>
entry_gender char(1)
entry_company varchar(32)
entry_firstname varchar(32)
entry_lastname varchar(32)
entry_street_address varchar(64)
entry_suburb varchar(32)
entry_postcode varchar(10)
entry_city varchar(32)
entry_state varchar(32)
entry_country_id integer(5) <fk2>
entry_zone_id integer(5) <fk1>
orders_id = orders_id
orders
orders_id integer(5) <pk>
customers_id integer(5) <fk1>
customers_name varchar(64)
customers_street_address varchar(64)
customers_suburb varchar(32)
customers_city varchar(32)
customers_postcode varchar(10)
customers_state varchar(32)
customers_country varchar(32)
customers_telephone varchar(32)
customers_email_address varchar(96)
customers_address_format_id integer(5) <fk3>
delivery_name varchar(64)
delivery_street_address varchar(64)
delivery_suburb varchar(32)
delivery_city varchar(32)
delivery_postcode varchar(10)
delivery_state varchar(32)
delivery_country varchar(32)
delivery_address_format_id integer(5) <fk2>
payment_method varchar(12)
cc_type varchar(20)
cc_owner varchar(64)
cc_number varchar(32)
cc_expires varchar(4)
last_modified datetime
date_purchased datetime
shipping_cost decimal(10,2)
shipping_method varchar(32)
orders_status varchar(10)
orders_date_finished datetime
comments text
currency char(3)
currency_value decimal(16,6)
orders_products
orders_products_id integer(5) <pk>
orders_id integer(5) <fk1>
products_id integer(5) <fk2>
products_name varchar(64)
products_price decimal(10,2)
final_price decimal(10,2)
products_tax decimal(9,4)
products_quantity integer(2)
orders_status
orders_status_id integer(5) <pk>
language_id integer(5) <pk>
orders_status_name varchar(32)
orders_products_id = orders_products_id
orders_products_attributes
orders_products_attributes_id integer(5) <pk>
orders_id integer(5) <fk1>
orders_products_id integer(5) <fk2>
products_options
products_options_values
options_values_price decimal(10,2)
price_prefix char(1)
countries_id = zone_country_id
countries_id = entry_country_id
zone_id = entry_zone_id
zones_to_geo_zones
association_id integer(5) <pk>
zone_country_id integer(5) <fk1>
zone_id integer(5) <fk3>
geo_zone_id integer(5) <fk2>
last_modified datetime
date_added datetime
countries
countries_id integer(5) <pk>
countries_name varchar(64)
countries_iso_code_2 char(2)
countries_iso_code_3 char(3)
address_format_id integer(5)
zone_id = zone_id
geo_zone_id = geo_zone_id
countries_id = zone_country_id
address_format_id = customers_address_format_id
orders_id = orders_id
geo_zones
geo_zone_id integer(5) <pk>
geo_zone_name varchar(32)
geo_zone_description varchar(255)
last_modified datetime
date_added datetime
zones
zone_id integer(5) <pk>
zone_country_id integer(5) <fk>
zone_code varchar(5)
zone_name varchar(32)
address_format
address_format_id integer(5) <pk>
address_format varchar(128)
address_summary varchar(48)
zone_id = tax_zone_id
address_format_id = delivery_address_format_id
tax_rates
tax_rates_id integer(5) <pk>
tax_zone_id integer(5) <fk2>
tax_class_id integer(5) <fk1>
tax_priority integer(5)
tax_rate decimal(9,4)
tax_description varchar(255)
last_modified datetime
date_added datetime
tax_class
tax_class_id integer(5) <pk>
tax_class_title varchar(32)
tax_class_description varchar(255)
last_modified datetime
date_added datetime
tax_class_id = tax_class_id